

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM



LISTING SERVICE

LISTING No. 2440-2270:0503

Page 1 of 1

CATEGORY: 2440 -- INSULATION

LISTEE: ROCKWOOL8024 Esquesing Line, Milton, ON L9T 6W3 Canada
Contact: Yuddish Manna (905) 875-5724
Email: list.cert@rockwool.com

DESIGN: ROCKWOOL TOPROCK® DD, available in 2" to 6" thick in 1/2" increments. TOPROCK® DD is a dual-density uncoated stone wool insulation board and classified as a thermal barrier. Top layer density is 13.75 lb/ft³ with bottom layer density of 10 lb/ft³ for 2" to 2.5" thick and 9.36 lb/ft³ for 3" to 6" thick.

Refer to listee's installation instructions and product data sheets.

RATING: Tested in accordance with ASTM E84 and ASTM E136

Flame Spread Index: 0
Smoke Developed Index: 0
Noncombustible material

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, rating, and SFM label.

APPROVAL: Listed as insulation for use in building construction when in compliance with the California Building Code. Refer to listee's Installation Instruction Manual for details.

11-20-20 VWW



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other

Date Issued: **July 01, 2021**

Listing Expires **June 30, 2022**

Authorized By: **DAVID CASTILLO, M.E., F.P.E.**
Fire Engineering Division